



Design by King & Miranda

FEATURES

- Dehumidification capacity: 28l/24h
- Tank capacity: 3,5 l
- Digital control
- LCD Display
- Full tank alarm
- Constant condensation disposal
- Electronic defrosting device
- Hidden tank with push-pull closing panel
- Water tank with handle, for easier transport and emptying
- Visible water level
- Hidden handle
- Wheels
- Cable winder
- For rooms up to: 120 m³



PURE SYSTEM 3


Triple filtration system which combines the filter with activated carbons (eliminates odors and deactivates any potentially harmful gases) HEPA filter (retains fine dust with a few microns diameter)

Photo catalytic filter (sterilizes air by eliminating a high percentage of viruses and bacteria).



DIGITAL CONTROL

Multifunction electronic panel, to set the desired humidity level and activate the Drying mode; moreover, Aquaria is equipped with back-lit LCD display to view humidity level and ambient temperature.



LARGE TANK

The tank contains 3.5 l and it can be easily extracted.



NON-STOP OPERATING

The constant condensation disposal, which can be selected on the control panel, allows uninterrupted dehumidification.



BACK CABLE WINDER

Cable winder to tidily put the product away.



		AQUARIA 28
	Code	01646
	EAN	8021183016468
Dehumidification capacity (2)	l/24h	28
Heating power	W	-
Power absorption in dehumidification mode (1)	W	425
Max. power absorption in dehumidification mode (2)	W	510
Max. power absorption in dehumidification+heating mode (2)	W	-
Fan speed		1
Tank capacity	l	3,5
Air volume (max)	m³/h	285
Dimensions (W x H x D)	mm	280 x 545 x 385
Gift box Dimensions (W x H x D)	mm	330 x 580 x 435
Sound level	db(A)	42
Weight	Kg	18
Refrigerant gas / Charge	Type / kg	R134A / 0,160 / 1430
Power supply	V-F-Hz	230 - 1 - 50
Power supply min - max	V	207 / 264
Air filter		✓
Carbon filter		✓
Fotocatalytic filter		✓
HEPA filter		✓
Continuous operation with hose		✓
Mechanical controls		
Digital control		✓
Mechanical Humidostat		
Digital Humidostat		✓
Display LCD		✓
Backlight LED Display		✓
Indoor humidity visualizer		✓
Indoor temperature visualizer		✓
Full tank alarm		✓
Defrosting device		✓
Mot gas defrosting system		
Dehumidifying + heating function		
Handle		✓
Wheels		✓
Tank with push-pull locking		✓
Tank with Handle		✓
Visible water level		✓
Wall mounting kit		

(1) DB 27°C - WB 21°C (27°C - 60% RH)

(2) DB 32°C - WB 29°C (32°C - 80% RH)