

# AQUARIA 22 - THERMO 22

AQUARIA 22 Code 01644

AQUARIA THERMO 22 Code 01645



AQUARIA 22

AQUARIA THERMO 22

Design by King & Miranda

## FEATURES

- Dehumidification capacity: 22l/24h
- Tank capacity: 3,5 l
- Electrical Resistance 1000W
- Digital control
- LCD Display
- Full tank alarm
- Constant condensation disposal
- Electronic defrosting device
- Hidden tank with push-pull closing panel
- Water tank with handle, for easier transport and emptying
- Visible water level
- Hidden handle
- Wheels
- Cable winder
- For rooms up to: 90 m<sup>3</sup> (Aquaria 22)
- For rooms up to: 100 m<sup>3</sup> (Aquaria Thermo 22)



### PURE SYSTEM 3

Triple filtration system which combines the filter with activated carbons (eliminates odors and deactivates any potentially harmful gases) HEPA filter (retains fine dust with a few microns diameter)

Photo catalytic filter (sterilizes air by eliminating a high percentage of viruses and bacteria).



### SUPER DEHUMIDIFICATION (only thermo 22)

Combines dehumidification with heating thanks to a 1000 W electrical element that significantly reduces dehumidification time.



### DIGITAL CONTROL

Multifunction electronic panel, to set the desired humidity level and activate the Drying mode; moreover, Aquaria is equipped with back-lit LCD display to view humidity level and ambient temperature.



### NON-STOP OPERATING

The constant condensation disposal, which can be selected on the control panel, allows uninterrupted dehumidification.



### LARGE TANK

The tank contains 3.5 l and it can be easily extracted.



### BACK CABLE WINDER

Cable winder to tidily put the product away.



|  |                   | AQUARIA 22           | AQUARIA THERMO 22    |
|--|-------------------|----------------------|----------------------|
|  | Code              | 01644                | 01645                |
|  | EAN               | 8021183016444        | 8021183016451        |
| Dehumidification capacity (2)                              | l/24h             | 22                   | 22                   |
| Heating power  | W                 | -                    | 1000                 |
| Power absorption in dehumidification mode (1)              | W                 | 250                  | 250                  |
| Max. power absorption in dehumidification mode (2)         | W                 | 295                  | 295                  |
| Max. power absorption in dehumidification+heating mode (2) | W                 | -                    | 1315                 |
| Fan speed  |                   | 1                    | 1                    |
| Tank capacity  | l                 | 3,5                  | 3,5                  |
| Air volume ( max )   | m <sup>3</sup> /h | 230                  | 250                  |
| Dimensions ( W x H x D )                                   | mm                | 280 x 545 x 385      | 280 x 545 x 385      |
| Gift box Dimensions ( W x H x D )                          | mm                | 330 x 580 x 435      | 330 x 580 x 435      |
| Sound level  | db(A)             | 40                   | 40                   |
| Weight   | Kg                | 17                   | 17                   |
| Refrigerant gas / Charge                                   | Type / kg         | R134A / 0,175 / 1430 | R134A / 0,175 / 1430 |
| Power supply   | V-F-Hz            | 230 - 1 - 50         | 230 - 1 - 50         |
| Power supply min - max                                     | V                 | 198 / 264            | 198 / 264            |
| Air filter   |                   | ✓                    | ✓                    |
| Carbon filter  |                   | ✓                    | ✓                    |
| Fotocathalitic filter                                      |                   | ✓                    | ✓                    |
| HEPA filter  |                   | ✓                    | ✓                    |
| Continuous operation with hose                             |                   | ✓                    | ✓                    |
| Mechanical controls  |                   |                      |                      |
| Digital control  |                   | ✓                    | ✓                    |
| Mechanical Humidostat                                      |                   |                      |                      |
| Digital Humidostat   |                   | ✓                    | ✓                    |
| Display LCD  |                   | ✓                    | ✓                    |
| Backlight LED Display                                      |                   |                      | ✓                    |
| Indoor humidity visualizer                                 |                   | ✓                    | ✓                    |
| Indoor temperature visualizer                              |                   | ✓                    | ✓                    |
| Full tank alarm  |                   | ✓                    | ✓                    |
| Defrosting device  |                   | ✓                    | ✓                    |
| Mot gas defrosting system                                  |                   |                      |                      |
| Dehumidifying + heating function                           |                   |                      | ✓                    |
| Handle   |                   | ✓                    | ✓                    |
| Wheels   |                   | ✓                    | ✓                    |
| Tank with push-pull locking                                |                   | ✓                    | ✓                    |
| Tank with Handle   |                   | ✓                    | ✓                    |
| Visible water level  |                   | ✓                    | ✓                    |
| Wall mounting kit  |                   |                      |                      |

(1) DB 27°C - WB 21°C ( 27°C - 60% RH )

(2) DB 32°C - WB 29°C ( 32°C - 80% RH )