

# DOLCECLIMA+®

The **most efficient** portable air conditioner of the range, Class **A+**.

DOLCECLIMA+ Cod. 01371



Italian Design by Dario Tanfoglio

## FEATURES

Cooling capacity: 11.000 BTU/h\*\*\*  
Nominal cooling capacity: 2,6 kW\*\*\*\*  
Energy Class: **A+**  
Sound power: **38 dB (A)†**  
Rated energy efficiency index: EER 3,1\*\*\*\*  
No tank: automatic condensation disposal  
Multifunction remote control  
LCD Display  
Timer 12h  
Practical side handles  
Wheels

## FUNCTIONS

- Fan mode:** Adjustable 2 fan speed. Fan only mode can also be used.
- Dehumidification mode**
- Auto mode:** automatic operation which regulates cooling in relation to the ambient temperature to optimize energy consumption.
- Sleep mode:** gradually increases the temperature set and ensures reduced noise for greater wellbeing at night.
- Turbo mode:** Maximum fan speed. Extra cool.



### SILENT SYSTEM

Up to 10% \* quieter at minimum speed, with a sound pressure of only 38 dB (A)\*\*.



### REMOTE CONTROL

Multifunction remote control.



### GOODNIGHT SLEEP

Thanks to Silent System technology, it is also suitable for the bedroom.

# A+

### HIGH EFFICIENCY TECHNOLOGY

Energy Class A+ and up to 15% reduced consumption.\*

\* Internal laboratory tests on traditional Olimpia Splendid range  
\*\* Declaration of test data in a semi anechoic chamber at a distance of 2m, minimum pressure fan only  
\*\*\* 35°C/80%RH  
\*\*\*\* In accordance with regulation EN14511

			DOLCECLIMA+®
Product code			01371
Rated output power for cooling (1)	P rated	kW	2,6
Maximum cooling capacity (35°C / 80%UR)		BTU/h	11000
Rated power input for cooling (1)	PEER	kW	0,8
Nominal absorption in cooling mode (1)		A	3,7
Rated efficiency energy ratio (1)	EERd		3,1
Energy Efficiency Class in cooling mode (1)			
Thermostat off mode power consumption	PTO	W	29,0
Standby mode power consumption (EN 62301)	PSB	W	1,0
Hourly electricity consumption for single duct (1) cooling mode	QSD	kWh/h	0,8
Power supply		V-F-Hz	230-1-50
Power supply min / max		V	198 / 264
Power absorption in cooling mode (1)		W	865
Maximum absorption in cooling mode (1)		A	3,84
Dehumidification capacity		l/h	1,0
Room air volume (max/med/min)		m³/h	410 / 345 / 255
Outdoor air volume		m³/h	445 / 340
Fan speeds			3
Flexible pipe (length x diameter)		mm	1500 x 120
Maximum remote control range (distance / angle)		m / °	8 / ±80°
Dimensions ( W x H x D ) (without packaging)		mm	460 x 767 x 395
Dimensions ( W x H x D ) (with packaging)		mm	484 x 852 x 448
Weight (without packing)		Kg	29
Weight (with packing)		Kg	33
Sound pressure level (6)	LWA	dB(A)	61
Sound power level (indoor only) (EN 12102)		dB(A)	38-48
Protection level			IP 10
Refrigerant gas*		Tipo	R410A
Global warming potential of refrigerant	GWP	kgCO2 eq.	2088
Refrigerant gas charge		kg	0,45
Maximum operating pressure		MPa	3,60
Maximum operating pressure (low pressure side)		MPa	2,10
Power cable (N° pole x section mm²)			3 x 1,5
Fuse			10AT

LIMITS OF OPERATING CONDITIONS

Indoor Ambient Temperature	Maximum temperature in cooling	DB 35°C - WB 32°C
	Minimum temperature in cooling	DB 16°C
	Maximum temperature in heating*	DB 27°C - WB 19°C
	Minimum temperature in heating*	DB 7°C
Outdoor Ambient Temperature	Maximum temperature in cooling	DB 43°C - WB 32°C
	Minimum temperature in cooling	DB 18°C - WB 16°C
	Maximum temperature in heating*	DB 27°C - WB 19°C
	Minimum temperature in heating*	DB 7°C

(1) TEST CONDITIONS: data refers to regulation EN14511  
\*hermetically sealed equipment containing fluorinated gas