EVERYTHING YOU NEED IN A SINGLE SYSTEM

Managing annual climate comfort and domestic hot water production with a single system allows you to simplify your home system, save on space and reduce energy consumption while increasing efficiency.





NEXYA MULTI ALL-IN-ONE

INCREASED EFFICIENCY THROUGH HEAT RECOVERY

Compared to traditional air conditioning and DHW production systems (separate management), parallel operation the recovery – in cooling mode – of the heat normally expelled by the external unit to produce DHW in the storage tank. Heat recovery can be total or partial, depending on the thermal power required by the boiler and the number of internal units active in providing climate comfort.

- Up to 3 rooms with air conditioning
- High wall installation
- DHW production





www.olimpiasplendid.com

: *

DOWNLOAD AREA



ITALIAN COMPANY

SINCE 1956

NEXYA Mono and multi-split air-to-air heat pump



A COMPLETE RANGE TO CREATE DIFFERENT SYSTEMS

The Nexya range is designed to meet a variety of intended uses (domestic or professional) and installation needs, with mono and Multi-Split solutions that include both internal wall units and cassette, duct or ceiling units.

Available in mono, dual, triple, quadruple and quintuple versions, they allow you to air condition up to 5 rooms with a single external motor.

MONO-SPLIT RANGE





NEXYA ENERGY E

HIGH INDOOR QUALITY OF AIR

The evaporator's high temperature sterilisation cycles prevent the formation of bacteria; the integrated ioniser neutralises the polluting agents dispersed in the air; the triple filtration (anti-dust, activated carbon and cold catalysts) remove any impurities.



High wall installation

• Wi-fi system included

		9	12				
NDO	OS-CEE	NHO9EI	OS-CEENH12EI				
DU	OS-SEE	NHO9EI	OS-SEENH12EI				
	2.6 kW	2.9 kW	3.5 kW	3.8 kW			
	A ^{····}	A ^{***}		A [®] ^A			
	EER 4,2	COP 4.5	EER 3.5	COP 3.9			



NEXYA S4 E

BREATHING WELLNESS

Automatically cleans and dries the evaporator, removing dust, mould and grease to ensure clean air in the room. The triple filtration (anti-dust, activated carbon and cold catalysts) also removes any impurities.



- High wall installation
- Wi-fi system included

	9		12		1	8	24		
ngo	OS-KENEH09EI		OS-KENEH12EI		OS-KENEH18EI		OS-KENEH24EI		
D	OS-SENEH09EI		OS-SENEH12EI		OS-SENEH18EI		OS-SENEH24EI		
	2.6 kW	2.9 kW	3.4 kW	3.7 kW	5,3 KW	4,9 kW	5,9 kW	6,0 kW	
	A ^{***}	A* D	A [~] A ⁺⁺⁺	A* ↑	A [∞] ^{A[∞]}	A* Î	A [∞] ^{A^{***}}	A* T	
	EER 3,6	COP 4,0	EER 3,28	COP 3,72	EER 3,4	COP 3,83	EER 3,28	COP 3,73	





	1	8	2	4	3	6	36	jΤ	48	BT
NDO	OS-CAN	CH18EI	OS-CEC	AH24EI	OS-CAN	CH36EI	OS-CAN	CHT36EI	OS-CEC/	ATH48EI
DD	OS-SEDAH18EI		OS-SEDAH24EI		OS-SEDAH36EI		OS-SEDAH36EI		OS-SEDAH48EI	
	5,3 kW	6,0 kW	7,1 kW	8,0 kW	9,9 kW	10,3 kW	9,2 kW	10,1 kW	14,1 kW	15,3 kW
	A ^w D	A T	A ^w D	A Î	A ^{···}	A Î D	A ^{···}	A D	A ^{**}	A [™] ↑ D
	EER 3,32	COP 3,72	EER 3,24	COP 3,99	EER 3,27	COP 3,73	EER 3,26	COP 3,75	EER 3,13	COP 3,72



_										
	18		24		36		36T		48T	
DDD	OS-CANCH18EI		OS-CECAH24EI OS-K/SANCH24EI		OS-CANCH36EI OS-K/SANCH36EI		OS-CANCHT36EI OS-K/SANCH36EI		OS-CECATH48EI OS-K/SANCH48EI	
≧ OS-K/SENA		NAH18EI								
	5,3 kW	5,3 kW	6,2 kW	7,6 kW	9,9 kW	11,1 kW	10 kW	11,1 kW	14,1 kW	16,1 kW
	A ^{**}	A D	A [~] ^A	A T	A ^w ^A	A T	A ^{***}	A T	A [~] I	A D
	EER 3,40	COP 3,76	EER 3,28	COP 4,01	EER 3,33	COP 3,71	EER 3,29	COP 3,71	EER 2,82	COP 3,52



	1	8	2	4	3	6	3(бТ	4	BT	<
ngo	OS-CAN	ICH18EI	OS-CEC	AH24EI	OS-CANCH36EI		OS-CANCHT36EI		OS-CECATH48EI		
B	OS-SAN	IFH18EI	OS-SAN	IFH24EI	OS-SAN	IFH36EI	OS-SAN	IFH36EI	OS-SAN	IFH48EI	\vdash
	5,3 kW	5,6 kW	6,8 kW	7,6 kW	10,1 kW	11,7 kW	10,1 kW	11,7 kW	14,1 kW	16,1 kW	\sim
	A ^w D	A Î	A ^{***}	A [*] ^A ^{***}	A [™] ↑	A [*] ↑	A [™] ↑	A Î	A [™] [↑]	A [*] ^A ^{***}	
	EER 3,64	COP 3,71	EER 3,30	COP 3,85	EER 3,31	COP 3,71	EER 3,25	COP 3,80	EER 2,81	COP 3,36	
	Nominal power in heating/cooling Energy efficiency class in heating/cooling (in a range between A+++ and D)										

NEXYA COMMERCIAL DUCT

COMPACT, WITH HIGH HEAD

The hallmark feature of the range is its compact size and easy installation. The ducted internal unit with static pressure available up to 160 Pa.

- Ducted installation
- Optional Wi-Fi

NEXYA COMMERCIAL CASSETTE

SUPERIOR CLIMATE COMFORT

The decorative panel, fitted with vents to expel the air, even in the corners, and optional independent flap control improves climate comfort.

- Recessed installation
- Optional Wi-Fi

NEXYA COMMERCIAL CEILING

- Wall installation
- Optional Wi-Fi

MULTI-SPLIT RANGE



NEXYA MULTI ALL-IN-ONE

High wall indoor unit for **up to 3 rooms** Indoor unit storage tank for DHW production

ODU	OS-CEMAH27EI
IDU	OS-SENEH09EI
IDU	OS-SENEH12EI
IDU	OS-SENEH18EI
DHW	02589



