



## Controls

### INDRZ

#### Addressing of the Modbus control kit

Addressing of TR commands and B0872 commands required for management via Modbus connection with SiOS Control, Bticino MyHome and any other home automation/BMS system that communicates via Modbus. Can be done on site by the installer or at the factory (specify when ordering).



### B0872

#### On-board autonomous flat touch control kit

Backlit display with desired temperature display, real-touch buttons, selection of the operating mode and ventilation speed. Command with adjustable room thermostat, operating modes (ventilation, summer, winter, automatic) and ventilation programme (silent, auto, maximum, night), minimum water probe function. It has one input for the contact presence sensor connection and two 230VAC outputs for the control of 2 solenoid valves. Through the user interface it is possible to add a correction on the read room temperature. Remote control included. Can be remotely controlled by combination of keys for connection with Modbus RS485 ASCII or RTU protocol.

**Combination with B0736 command, MyHome by Bticino and SiOS Control is always possible (mandatory pairing for use with Bi2 SLI and SLIR, in this case, remote control not working).** Colour RAL 9003.



Compatible with:	SL	SLR	SLI	SLIR
Bi2 SMART S1	○	○	○	○
Bi2 NAKED			○	○

### B0873

#### Electronic contacts/0-10V remote control kit

Electronic interface card for management and control via 0-10V analog input or contacts (for radiant fan coil units use the contact mode and check that the management system interfaced to the B0756 card supports the control logic of Olimpia Splendid radiant technology). It has a 230VAC output for control of a solenoid valve and a water probe inlet with the function of a minimum probe (for both modes of remote control). **Can be combined with B0921 contact touch wall-mounted thermostat kit (not for radiant fan coil units) or with third party home automation/BMS systems that can be interfaced to contacts or via 0-10V signal.** Colour RAL 9003.



Compatible with:	SL	SLR	SLI	SLIR
Bi2 SMART S1	○	○	○	○
Bi2 NAKED			○	○

### B0736

#### Wall-mounted Modbus chrono-thermostat kit

For MODBUS, RS485 connection. Up to 30 units can be controlled. Selection of the desired temperature selection, operating mode, ventilation speed, manual/chrono-thermostat mode. Ambient probe inserted in the control. Backlit LCD display. Presence sensor contact. The control is equipped with a dual insulated 230V/12 VAC power supply transformer and a backup battery. Wall mounting with hole interaxis compatible with standard 503 formwork box.

**Can be combined with the controls TR, B0872 and SiOS Control.**



Compatible with:	SL	SLR	SLW
Bi2 AIR	TR	TR	TR
Bi2 SMART S1	○	○	
Bi2 WALL			TR
Bi2 NAKED			○

### B0921

#### Contact touch wall-mounted thermostat kit

Digital thermostat with room probe, backlit display and touch buttons. Semi-recessed installation (15 mm out of the wall) in boxes with 60 mm round or square interaxis screws. Room temperature display, adjustment of the desired room temperature from 5°C to 35°C, setting of the "cooling" or "heating" mode, setting of the fan speed (Min/Med/Max). 230V AC power supply, it has a solenoid valve output and a water temperature probe input. **Can be paired with AR and B0873 remote control cards.**



Compatible with:	SL	SLR	SLW
Bi2 AIR	AR	—	AR
Bi2 SMART S1	○	—	
Bi2 WALL			AR
Bi2 NAKED			○

**B1135**

**Wall-mounted thermostat kit**

Wall thermostat kit. Desired temperature selection, operating mode, ventilation speed. Ambient probe inserted in the control. LCD display. Wall mounting with hole interaxis compatible with standard 503 formwork box. For 0-10 V connection. Outputs: 1 EC~230V 0-10Vdc motor, 1 ON/OFF valve, 1 heating element, 1 minimum probe for water temperature control.



Compatible with:

Bi2 DUCTED	<input type="radio"/>
------------	-----------------------

**B1136**

**Wi-Fi touch wall thermostat kit**

Wi-Fi wall thermostat kit. Selection of desired temperature, operating mode, ventilation speed, weekly timed thermostat mode configurable from dedicated app. Ambient probe inserted in the control. LCD display. Wall mounting with hole interaxis compatible with standard 503 formwork box. For 0-10 V connection. Outputs: 1 EC~230V 0-10Vdc motor, 1 ON/OFF valve, 1 heating element, 1 minimum probe for water temperature control.



Compatible with:

Bi2 DUCTED	<input type="radio"/>
------------	-----------------------

**B1130**

**Wireless kit**

Installed on the electronics of Bi2 terminals, it allows controlling them using the OS Smart System application. The kit can be supplied for installation on site; alternatively, it can be fitted to the terminal directly at the factory. A kit must be provided for each terminal that you want to control with the application (in the case of Bi2 Naked, only one kit for each B0736).



Compatible with:

	SL	SLR		SLW
Bi2 AIR + B0872	<input checked="" type="radio"/>	<input checked="" type="radio"/>	Bi2 WALL	<input checked="" type="radio"/>
Bi2 SMART S1	<input type="radio"/>	<input type="radio"/>		SLI SLIR
			Bi2 NAKED + B0872 + B0736	<input type="radio"/> <input type="radio"/>

**COMPATIBILITY WITH CONTROLS FROM OTHER MANUFACTURERS**

To expand the control possibilities, the Olimpia Splendid terminal units are compatible with a selection of thermostats and advanced control systems, featuring wireless connections and applications for tablets and smartphones. You can consult the compatibility sheets in the download area of the [Olimpiaspplendid.it](http://Olimpiaspplendid.it) website.

## Electrical kits

**B0633**

**LH-RH connection rotation extension kit**

Electrical connection cable of the power supply and motor sensor for the installation of fan coil units in which the position of the hydraulic connection is rotated from left to right.



Compatible with:

	SL	SLR		SLI	SLIR
Bi2 SMART S1	<input type="radio"/>	<input type="radio"/>	Bi2 NAKED	<input type="radio"/>	<input type="radio"/>

**B0839**






**LH-RH connection rotation extension kit**

Electrical connection cable of the power supply and motor sensor for the installations in which the position of the hydraulic connection is rotated from left to right.



Compatible with:

	SL	SLR
Bi2 AIR	<input type="radio"/>	<input type="radio"/>

<b>B1137</b> <small>new</small>	<b>Water temperature probe</b> Water temperature probe kit for activating ventilation only when the desired water temperature is reached Compatible with: <div> <div>Bi2 DUCTED</div> <div>○</div> </div>	
<b>B1146</b> <small>new</small>	<b>Integration electric heating element</b> 1000W integration electric heating element kit for heating 230/1/50 (V/ph/Hz), factory configurable on request. Compatible with: <div> <div>Bi2 DUCTED</div> <div>220</div> </div>	
<b>B1147</b> <small>new</small>	<b>Integration electric heating element</b> 1500W integration electric heating element kit for heating 230/1/50 (V/ph/Hz), factory configurable on request. Compatible with: <div> <div>Bi2 DUCTED</div> <div>320/420</div> </div>	
<b>B1148</b> <small>new</small>	<b>Integration electric heating element</b> 2000W integration electric heating element kit for heating 230/1/50 (V/ph/Hz), factory configurable on request. Compatible with: <div> <div>Bi2 DUCTED</div> <div>520/620</div> </div>	
	<b>Integration electric heating element</b> 3000W integration electric heating element kit for heating 230/1/50 (V/ph/Hz), factory configurable on request. Compatible with: <div> <div>Bi2 DUCTED</div> <div>720/820</div> </div>	
<b>B1149</b> <small>new</small>	Bi2 DUCTED	720/820
<b>B1150</b> <small>new</small>	Bi2 DUCTED	1020
<b>B1151</b> <small>new</small>	Bi2 DUCTED	1120/1220

○ Optional accessory | — Accessory not compatible

Please note: optional accessories are available for purchase in conjunction with all models of the terminal. When compatibility is only possible with certain sizes or models, the information is shown in the table.

# Condensation drain kit

## B0983

### Condensation pump kit

The optional kit for condensation pump allows solving the drain problem even where the slopes do not allow a natural discharge of the water (see details in the installation manual).

Compatible with:

SL

Bi2 WALL	≥ 1000
----------	--------



## B1142

### Condensation pump kit for vertical installation

The optional kit for condensation pump allows solving the drain problem even where the slopes do not allow a natural discharge of the water. The kit comes with an additional condensate drip tray for vertical installation.

Compatible with:

Bi2 DUCTED	<input type="radio"/>
------------	-----------------------



## B1143

### Condensation pump kit for horizontal installation

The optional kit for condensation pump allows solving the drain problem even where the slopes do not allow a natural discharge of the water.

Compatible with:

Bi2 DUCTED	<input type="radio"/>
------------	-----------------------



# Hydraulics kit

## B0832

### 2-way valve group kit with 4-wire actuator

It consists of a valve (with thermoelectric actuator and limit switch) and a lockshield. The former allows the control of the thermal emission of the fan coil unit by intercepting the passage of the water; the lockshield allows the balancing of the load losses of the system. This kit becomes mandatory in the SLR version except in the case where a 3-way valve kit is used or if there is a manifold with thermoelectric heads. Please note: for all terminal models, if wall-mounted thermostats are not used, the installation of 2- or 3-way valves is recommended for optimal cooling operation and for the on/off of a secondary circulator or heat generator.

Compatible with:

SL

SLR

Bi2 AIR	<input type="radio"/>	<input type="radio"/>
Bi2 SMART S1	<input type="radio"/>	<input type="radio"/>

SLI

SLIR

Bi2 NAKED	<input type="radio"/>	<input type="radio"/>
-----------	-----------------------	-----------------------



## B0834

### 3-way valve group kit with 4-wire actuator

It consists of a three-way valve switch (with thermoelectric actuator and limit switch) and a lockshield. The former allows the control of the thermal emission of the fan coil unit by intercepting the passage of the water; the lockshield allows the balancing of the load losses of the system; the by-pass maintains the circulation of the water in the system. This kit is an alternative to the 2-way solenoid valve kit (mandatory in the SLR version).

Please note: for all terminal models, if wall-mounted thermostats are not used, the installation of 2- or 3-way valves is recommended for optimum cooling operation and for the on/off of a secondary circulator or heat generator.

Compatible with:

SL

SLR

Bi2 AIR	<input type="radio"/>	<input type="radio"/>
Bi2 SMART S1	<input type="radio"/>	<input type="radio"/>

SLI

SLIR

Bi2 NAKED	<input type="radio"/>	<input type="radio"/>
-----------	-----------------------	-----------------------



## B0205

### Manual 2-way valve group kit

It consists of a valve and a lockshield, the former allows the fan coil to be excluded from the system manually, while the lockshield allows the balancing of the system load losses. Permitted if solenoid valves on the manifold are managed by the Bi2 control kit.

Compatible with:

SL

SLR

Bi2 AIR	<input type="radio"/>	<input type="radio"/>
Bi2 SMART S1	<input type="radio"/>	<input type="radio"/>

SLI

SLIR

Bi2 NAKED	<input type="radio"/>	<input type="radio"/>
-----------	-----------------------	-----------------------



# Hydraulics kit

**B0204**

## Manual 2-way valve insulation kit

Prevents condensation during the cooling operation (already included in the thermoelectric hydraulic kits).



Compatible with:	SL	SLR		SLI	SLIR
Bi2 AIR	<input type="radio"/>	<input type="radio"/>	Bi2 NAKED	<input type="radio"/>	<input type="radio"/>
Bi2 SMART S1	<input type="radio"/>	<input type="radio"/>			

**B0200**

## Adapter connection kit for 1/2" gas thread

It allows the conversion of the 3/4" Eurokonus connection of the Bi2 into a standard 1/2" gas thread connection.



Compatible with:	SL	SLR		SLI	SLIR
Bi2 AIR	<input type="radio"/>	<input type="radio"/>	Bi2 NAKED	<input type="radio"/>	<input type="radio"/>
Bi2 SMART S1	<input type="radio"/>	<input type="radio"/>			

**B0201**

## Adapter connection kit for 3/4" gas thread

It allows the conversion of the 3/4" Eurokonus connection of the Bi2 into a standard 3/4" gas thread connection.



Compatible with:	SL	SLR		SLI	SLIR
Bi2 AIR	<input type="radio"/>	<input type="radio"/>	Bi2 NAKED	<input type="radio"/>	<input type="radio"/>
Bi2 SMART S1	<input type="radio"/>	<input type="radio"/>			

**B0203**

## Eurokonus 90° bending connection kit

Facilitates connection in case of hydraulic connections with wall-mounted pipes.



Compatible with:	SL	SLR		SLI	SLIR
Bi2 AIR	<input type="radio"/>	<input type="radio"/>	Bi2 NAKED	<input type="radio"/>	<input type="radio"/>
Bi2 SMART S1	<input type="radio"/>	<input type="radio"/>			

**B1140**

## 2-way valve kit for horizontal installation

Consisting of a 2-way valve with thermoelectric actuator. The valve allows control of the thermal emission of the terminal by intercepting the passage of water. This kit is supplied as standard with the additional horizontal tray for collecting condensation.

Compatible with:

Bi2 DUCTED	<input type="radio"/>
------------	-----------------------



**B1141**

## 2-way valve kit for vertical installation

Consisting of a 2-way valve with thermoelectric actuator. The valve allows control of the thermal emission of the terminal by intercepting the passage of water. This kit is supplied as standard with the additional vertical tray for collecting condensation.

Compatible with:

Bi2 DUCTED	<input type="radio"/>
------------	-----------------------



**B1138**

## 3-way valve kit for horizontal installation

Consisting of a 3-way valve with thermoelectric actuator. The valve allows control of the thermal emission of the terminal by intercepting the passage of water. This kit is supplied as standard with the additional horizontal tray for collecting condensation.

Compatible with:

Bi2 DUCTED	<input type="radio"/>
------------	-----------------------



**B1139**

## 3-way valve kit for vertical installation

Consisting of a 3-way valve with thermoelectric actuator. The valve allows control of the thermal emission of the terminal by intercepting the passage of water. This kit is supplied as standard with the additional vertical tray for collecting condensation.

Compatible with:

Bi2 DUCTED	<input type="radio"/>
------------	-----------------------



☐ Optional accessory | — Accessory not compatible

Please note: optional accessories are available for purchase in conjunction with all models of the terminal. When compatibility is only possible with certain sizes or models, the information is shown in the table.

### B1145

#### Additional condensate collection tray kit, horizontal version

Auxiliary condensation collection tray suitable for horizontal installations. (Supplied as standard with the B1140 and B1138 kits)

Compatible with:

Bi2 DUCTED	<input type="radio"/>
------------	-----------------------



### B1144

#### Additional condensate collection tray kit, vertical version

Auxiliary condensation collection tray suitable for vertical installations. (Supplied as standard with the B1141 and B1139 kits)

Compatible with:

Bi2 DUCTED	<input type="radio"/>
------------	-----------------------



## Aesthetic kits

#### Floor mounting bracket kit

Kit for support brackets and floor mounting of the fan coil unit (glass front applications or on non-load-bearing walls). It also has the function of aesthetic kit for covering (white colour RAL 9003) and is therefore not compatible with the aesthetic kit of feet for covering.

Compatible with:

		SL	SLR
<b>B0852</b>	Bi2 AIR	≤800	≤800
<b>B0938</b>	Bi2 SMART S1	<input type="radio"/>	<input type="radio"/>



#### Floor mounting bracket kit

Kit for support brackets and floor mounting of the fan coil unit (glass front applications or on non-load-bearing walls). To be used in conjunction with the B0874 kit. Increases the fan coil unit depth by 17 mm (18 mm if with back panel)

Compatible with:

		SL	SLR
<b>B0875</b>	Bi2 AIR	≥1100	≥1100



#### Aesthetic kit feet for covering

Aesthetic kit containing two feet for covering any pipes coming from the floor. Available in the colour white RAL 9003.

Compatible with:

		SL	SLR
<b>B0853</b>	Bi2 AIR	≤800	≤800
<b>B0874</b>	Bi2 AIR	≥1100	≥1100



		SL	SLR
<b>B0937</b>	Bi2 SMART S1	<input type="radio"/>	<input type="radio"/>

#### Aesthetic ceiling feet kit

Aesthetic kit containing two feet for covering any pipes coming from the wall. Specially designed to maximise the space available for the pipes in the case of ceiling installation. Available in white RAL 9003.

Compatible with:

		SL	SLR
<b>B0982</b>	Bi2 SMART S1	<input type="radio"/>	—



### Back panel

In white painted sheet metal (RAL 9003), for glass front applications.



Compatible with:

		SL	SLR
<b>B0847</b>	Bi2 AIR	200	200
<b>B0848</b>	Bi2 AIR	400	400
<b>B0849</b>	Bi2 AIR	600	600
<b>B0850</b>	Bi2 AIR	800	800

		SL	SLR
<b>B0876</b>	Bi2 AIR	1100	1100
<b>B0876</b>	Bi2 AIR	1400	1400
<b>B0877</b>	Bi2 AIR	1600	1600

### Ceiling-mount kit (condensation trap)

Trap kit for the collection of the condensation in case of horizontal installation.



Compatible with:

		SL	SLR
<b>B0520</b>	Bi2 AIR - Bi2 SMART S1	200	—
<b>B0521</b>	Bi2 AIR - Bi2 SMART S1	400	—
<b>B0522</b>	Bi2 AIR - Bi2 SMART S1	600	—
<b>B0523</b>	Bi2 AIR - Bi2 SMART S1	800	—

		SL	SLR
<b>B0878</b>	Bi2 AIR	1100	—
<b>B0878</b>	Bi2 AIR	1400	—
<b>B0879</b>	Bi2 AIR	1600	—

## Kit for recess

### Formwork for recessed installation

Frame for vertical recessed installation (to be combined with the closing panel).



Compatible with:

		SLI	SLIR
<b>B0568</b>	Bi2 NAKED	200	200
<b>B0569</b>	Bi2 NAKED	400	400
<b>B0570</b>	Bi2 NAKED	600	600

		SLI	SLIR
<b>B0571</b>	Bi2 NAKED	800	800
<b>B0894</b>	Bi2 NAKED	≥ 1100	≥ 1100

### Radiant closing panel RAL 9003

Aesthetic panel for recessed radiant closing for vertical installation (mandatory kit, to be combined with the recessed formwork). Colour white RAL 9003.



Compatible with:

		SLI	SLIR
<b>B0950</b>	Bi2 NAKED	—	200
<b>B0951</b>	Bi2 NAKED	—	400
<b>B0952</b>	Bi2 NAKED	—	600

		SLI	SLIR
<b>B0953</b>	Bi2 NAKED	—	800
<b>B0954</b>	Bi2 NAKED	—	≥ 1100

### Closing panel RAL 9003

Aesthetic panel for recessed closing for vertical installation (to be combined with the recessed formwork). Colour white RAL 9003.



Compatible with:

		SLI	SLIR
<b>B0955</b>	Bi2 NAKED	200	—
<b>B0956</b>	Bi2 NAKED	400	—
<b>B0957</b>	Bi2 NAKED	600	—

		SLI	SLIR
<b>B0958</b>	Bi2 NAKED	800	—
<b>B0959</b>	Bi2 NAKED	≥ 1100	—

### Air delivery grille with airfoil profile

Kit for recessed false ceiling mounting.



Compatible with:

		SLI	SLIR
<b>B0550</b>	Bi2 NAKED	200	—
<b>B0551</b>	Bi2 NAKED	400	—
<b>B0552</b>	Bi2 NAKED	600	—
<b>B0553</b>	Bi2 NAKED	800	—

		SLI	SLIR
<b>B0880</b>	Bi2 NAKED	1100	—
<b>B0880</b>	Bi2 NAKED	1400	—
<b>B0881</b>	Bi2 NAKED	1600	—

**Air intake grille with airfoil profile**  
Kit for recessed false ceiling mounting.



Compatible with:

		SLI	SLIR
<b>B0559</b>	Bi2 NAKED	200	—
<b>B0560</b>	Bi2 NAKED	400	—
<b>B0561</b>	Bi2 NAKED	600	—
<b>B0562</b>	Bi2 NAKED	800	—

		SLI	SLIR
<b>B0882</b>	Bi2 NAKED	1100	—
<b>B0882</b>	Bi2 NAKED	1400	—
<b>B0883</b>	Bi2 NAKED	1600	—

**Intake kit**

Kit for false ceiling or roof hatch mounting. Not compatible with recessed frame. Channels the intake air from the intake grille to the fan coil.




Compatible with:

		SLI	SLIR
<b>B0194</b>	Bi2 NAKED	200	—
<b>B0195</b>	Bi2 NAKED	400	—
<b>B0196</b>	Bi2 NAKED	600	—
<b>B0197</b>	Bi2 NAKED	800	—

		SLI	SLIR
<b>B0888</b>	Bi2 NAKED	1100	—
<b>B0888</b>	Bi2 NAKED	1400	—
<b>B0889</b>	Bi2 NAKED	1600	—

**Telescopic top delivery plenum**

Not compatible with recessed frame. Channels the air from the fan coil to the delivery grille.



Compatible with:

		SLI	SLIR
<b>B0160</b>	Bi2 NAKED	200	—
<b>B0161</b>	Bi2 NAKED	400	—
<b>B0162</b>	Bi2 NAKED	600	—
<b>B0163</b>	Bi2 NAKED	800	—

		SLI	SLIR
<b>B0890</b>	Bi2 NAKED	1100	—
<b>B0890</b>	Bi2 NAKED	1400	—
<b>B0891</b>	Bi2 NAKED	1600	—

**Insulated 90° delivery plenum**

Not compatible with recessed frame. Channels the air from the fan coil to the delivery grille.



Compatible with:

		SLI	SLIR
<b>B0165</b>	Bi2 NAKED	200	—
<b>B0166</b>	Bi2 NAKED	400	—
<b>B0167</b>	Bi2 NAKED	600	—
<b>B0168</b>	Bi2 NAKED	800	—

		SLI	SLIR
<b>B0892</b>	Bi2 NAKED	1100	—
<b>B0892</b>	Bi2 NAKED	1400	—
<b>B0893</b>	Bi2 NAKED	1600	—

○ Accessorio opzionale | — Accessorio non compatibile

Please note: optional accessories are available for purchase in conjunction with all models of the terminal. When compatibility is only possible with certain sizes or models, the information is shown in the table.

## Ducting kit

**B1152**

**Insulated air delivery plenum kit with 1 circular connection**

Insulated air delivery plenum with 1 circular connection  $\varnothing$  200/180/160 mm.



Compatible with:

Bi2 DUCTED	220
------------	-----



**Insulated air delivery plenum kit with 2 circular connections**Insulated air delivery plenum with 2 circular connections  $\varnothing$  200/180/160 mm.Compatible with:

<b>B1153</b>	Bi2 DUCTED	320/420	<b>B1154</b>	Bi2 DUCTED	520/620
--------------	------------	---------	--------------	------------	---------

**B1155 Insulated air delivery plenum kit with 3 circular connections**Insulated air delivery plenum with 3 circular connections  $\varnothing$  200/180/160 mm.Compatible with:

Bi2 DUCTED	720/820
------------	---------

**Insulated air delivery plenum kit with 4 circular connections**Insulated air delivery plenum with 4 circular connections  $\varnothing$  200/180/160 mm.Compatible with:

<b>B1156</b>	Bi2 DUCTED	1020	<b>B1157</b>	Bi2 DUCTED	1120/1220
--------------	------------	------	--------------	------------	-----------

**B1158 Air extraction plenum kit with 1 circular connection**Non-insulated air extraction plenum with 1 circular connection  $\varnothing$  200/180/160 mm.Compatible with:

Bi2 DUCTED	220
------------	-----

**Air extraction plenum kit with 2 circular connections**Non-insulated air extraction plenum with 2 circular connections  $\varnothing$  200/180/160 mm.Compatible with:

<b>B1159</b>	Bi2 DUCTED	320/420	<b>B1160</b>	Bi2 DUCTED	520/620
--------------	------------	---------	--------------	------------	---------

**B1161 Air extraction plenum kit with 3 circular connections**Non-insulated air extraction plenum with 3 circular connections  $\varnothing$  200/180/160 mm.Compatible with:

Bi2 DUCTED	720/820
------------	---------

**Air extraction plenum kit with 4 circular connections**Non-insulated air extraction plenum with 4 circular connections  $\varnothing$  200/180/160 mm.Compatible with:

<b>B1162</b>	Bi2 DUCTED	1020
<b>B1163</b>	Bi2 DUCTED	1120/1220

**Straight insulated air delivery plenum kit**Compatible with:

<b>B1164</b>	Bi2 DUCTED	220	<b>B1167</b>	Bi2 DUCTED	720/820
<b>B1165</b>	Bi2 DUCTED	320/420	<b>B1168</b>	Bi2 DUCTED	1020
<b>B1166</b>	Bi2 DUCTED	520/620	<b>B1169</b>	Bi2 DUCTED	1120/1220

### Straight air extraction plenum kit



Compatible with:

<b>B1170</b>	Bi2 DUCTED	220
<b>B1171</b>	Bi2 DUCTED	320/420
<b>B1172</b>	Bi2 DUCTED	520/620

<b>B1173</b>	Bi2 DUCTED	720/820
<b>B1174</b>	Bi2 DUCTED	1020
<b>B1175</b>	Bi2 DUCTED	1120/1220

### 90° insulated air delivery plenum kit



Compatible with:

<b>B1176</b>	Bi2 DUCTED	220
<b>B1177</b>	Bi2 DUCTED	320/420
<b>B1178</b>	Bi2 DUCTED	520/620

<b>B1179</b>	Bi2 DUCTED	720/820
<b>B1180</b>	Bi2 DUCTED	1020
<b>B1181</b>	Bi2 DUCTED	1120/1220

### 90° air extraction plenum kit



Compatible with:

<b>B1182</b>	Bi2 DUCTED	220
<b>B1183</b>	Bi2 DUCTED	320/420
<b>B1184</b>	Bi2 DUCTED	520/620

<b>B1185</b>	Bi2 DUCTED	720/820
<b>B1186</b>	Bi2 DUCTED	1020
<b>B1187</b>	Bi2 DUCTED	1120/1220

### Telescopic extension kit 0-100 mm

Telescopic extension 0-100mm suitable for connection with all straight and 90° extraction and delivery plenums (not compatible with plenums with circular connections).



Compatible with:

<b>B1188</b>	Bi2 DUCTED	220
<b>B1189</b>	Bi2 DUCTED	320/420
<b>B1190</b>	Bi2 DUCTED	520/620

<b>B1191</b>	Bi2 DUCTED	720/820
<b>B1192</b>	Bi2 DUCTED	1020
<b>B1193</b>	Bi2 DUCTED	1120/1220

### Delivery grille kit

Air delivery grille without fixed fin filter in ABS, white RAL 9003



Compatible with:

<b>B1194</b>	Bi2 DUCTED	220
<b>B1195</b>	Bi2 DUCTED	320/420
<b>B1196</b>	Bi2 DUCTED	520/620

<b>B1197</b>	Bi2 DUCTED	720/820
<b>B1198</b>	Bi2 DUCTED	1020
<b>B1199</b>	Bi2 DUCTED	1120/1220

### Extraction grille kit

Air extraction grille with fixed fin filter in ABS, white RAL 9003.



Compatible with:

<b>B1200</b>	Bi2 DUCTED	220
<b>B1201</b>	Bi2 DUCTED	320/420
<b>B1202</b>	Bi2 DUCTED	520/620

<b>B1203</b>	Bi2 DUCTED	720/820
<b>B1204</b>	Bi2 DUCTED	1020
<b>B1205</b>	Bi2 DUCTED	1120/1220