

Decentralized HRV accessories



Download
Additional
information on
these accessories

B0838

External grille

High-quality ABS fixed external grille, resistant to impacts and UV rays. Colour RAL 9010. Diameter 100mm. Compatible with Sitali SFE 100.



B0837

Telescopic pipe

PVC telescopic pipe which adapts to the thickness of the wall. Diameter 100mm. Compatible with Sitali SFE 100.



B1119

Terminal unit 150 Silent

"Dnew 45dB), designed to reduce noise coming from outside. Suitable for particularly windy outdoor conditions. Made of RAL9010 pre-painted aluminium sheet, equipped with fireproof sound-absorbing mat, front inspection panel, drip trap and anti-insect net. Possibility of semi-recessed installation as well. Compatible with Sitali SF 150 S1.



Centralised HRV accessories

External air distribution

ABS ext grille

High-quality ABS fixed external grille, resistant to impacts and UV rays. Colour RAL 9010.



B1065

Diameter 100mm

B1066

Diameter 125mm

B1067

Diameter 150mm

Flex ALU ISO

Flexible pipe, 10m in length, made with aluminium/polyester/micro-perforated aluminium walls for air passage noise reduction and steel concertina wire. Polyester fibre thermal insulation coating (thickness 25mm/16kg/m³) and aluminium-coated polyolefin film outer protection.



B1068

Diameter 127mm

B1069

Diameter 160mm

Wall passage

Wall penetration kit with external terminal in galvanised sheet metal coated in RAL 9010 and fitted with sound-absorbing mat.



B1074

Diameter 125mm

B1075

Diameter 150mm

Telescopic pipe

PVC telescopic pipes which adapt to the thickness of the wall. (L=300-570 mm).



B1103

Diameter 100mm

B1104

Diameter 125mm

B1105

Diameter 150mm

EPE pipe

Insulated and soundproofed EPE pipe, with smooth interior and exterior; length 2m.



B1110

DN125 L=2m

B1114

DN150 L=2m

EPE 90 bend

Insulated and soundproofed EPE bend, with smooth interior and exterior.

B1111	DN125
B1115	DN150


EPE coupling

Coupling for connecting EPE pipe/EPE pipe, EPE pipe/EPE 90 bend.

B1112	DN125
B1116	DN150


EPE collar

Bracket collar and for connection of the EPE/ventilation unit pipe and EPE pipe/distribution plenum.

B1113	DN125
B1117	DN150



Internal air distribution

E-I designer vent

Extraction/inlet vent with flow rate adjustment module; front cover made of high-quality ABS; white RAL 9010. The adjustment module consists of removable concentric circles to define the desired volume of air.

B1058	Diameter 80mm
B1055	Diameter 100mm
B1056	Diameter 125mm
B1057	Diameter 150mm


FT-WHITE grille

Rectangular steel grille pre-coated in RAL 9010 white, with round perforated screen and magnetic attachment system.

B1070	Dimension 200x100mm
B1072	Dimension 300x100mm


FT-METAL grille

Rectangular steel grille with metallic finish, round perforated screen and magnetic attachment system.

B1071	Dimension 200x100mm
B1073	Dimension 300x100mm


B1059 Flex HDPE 75/63

Flexible 75/63 pipe with antimicrobial, antibacterial and antistatic treatment, made with high-density double polyethylene wall; corrugated on the outside and smooth on the inside; supplied with end caps; used to channel the air from the distribution plenum to the air inlet and extraction vents. Suitable for installation in concrete slab, false ceilings or on walls. Length 50 m.


B1054 FLEX HDPE 75/63 90° adaptor

90° angle adaptor, Ø125mm with 2 attachments Ø80mm (for Flex HDPE 75/63 duct), including 2 protection/end caps, length 250mm. Suitable for designer vents with 125mm diameter and extraction/inlet valves.



FLEX HDPE 75/63 hooks

Connection kit for Flex HDPE 75/63 pipe to make worksite installation easier. Available in packs of 12 in red or blue to identify the air flow direction.



B1076	Blue
B1077	Red

B1078 FLEX HDPE 75/63 90° bend

90° bend kit for Flex HDPE 75/63 pipe with sealing rings included.

**B1087 FLEX HDPE 75/63 coupling**

Coupling kit for Flex HDPE 75/63 pipe with sealing rings included.

**B1088 O-Ring FLEX HDPE 75/63**

O-ring kit for Flex HDPE 75/63 pipe (pack of 10).

**B1095 Plenum P Ø125mm - 4 outlets (for Flex HDPE)**

Distribution plenum, 1 inlet Ø125mm, 4 outlets Ø80mm (for Flex HDPE 75/63 duct) and 5 protection/end caps supplied.

**B1096 Plenum P Ø125mm - 6 outlets (for Flex HDPE)**

Distribution plenum, 1 inlet Ø125mm, 6 outlets Ø80mm (for Flex HDPE 75/63 duct) and 7 protection/end caps supplied.

**B1094 Plenum P Ø125mm - 10 outlets (for Flex HDPE)**

Distribution plenum, 1 inlet Ø125mm, 10 outlets Ø80mm (for Flex HDPE 75/63 duct) and 11 protection/end caps supplied.

**B1098 Plenum P Ø150mm - 10 outlets (for Flex HDPE)**

Distribution plenum, 1 inlet Ø150mm, 10 outlets Ø80mm (for Flex HDPE 75/63 duct) and 11 protection/end caps supplied.

**B1099 Plenum P Ø150mm - 15 outlets (for Flex HDPE)**

Distribution plenum, 1 inlet Ø150mm, 15 outlets Ø80mm (for Flex HDPE 75/63 duct) and 16 protection/end caps supplied.

**B1092 Plenum L 200x100mm - 1 coupling (for Flex HDPE)**

Inlet/extraction plenum, 1 fitting on the long side Ø80mm, complete with anti-mortar closure and 1 cap (for Flex HDPE 75/63 duct). Air flow adjustment via the CAL80 damper (on request).

**B1093 Plenum L 300x100mm - 2 couplings (for Flex HDPE)**

Inlet/extraction plenum, 2 fittings on the long side Ø80mm, complete with anti-mortar closure and 2 caps (for Flex HDPE 75/63 duct). Air flow adjustment via the CAL80 damper (on request).



B1101 Plenum P 200x100mm - 1 coupling (for Flex HDPE)

Inlet/extraction plenum, 1 rear fitting Ø80mm, complete with anti-mortar closure and 1 cap (for Flex HDPE 75/63 duct). Air flow adjustment via the CAL80 damper (on request).


B1102 Plenum P 300x100mm - 2 couplings (for Flex HDPE)

Inlet/extraction plenum, 2 fittings on the rear Ø80mm, complete with anti-mortar closure and 2 caps (for Flex HDPE 75/63 duct). Air flow adjustment via the CAL80 damper (on request).


B1091 Plenum LCS 200x100mm - 1 coupling (for Flex HDPE)

Inlet/extraction plenum, 1 fitting on the short side Ø80mm, complete with anti-mortar closure and 1 cap (for Flex HDPE 75/63 duct).


B1089 Plenum L 140x140mm - 1 coupling (for Flex HDPE)

Inlet/extraction plenum with 1 side coupling Ø80mm (for HDPE 75/63). Including anti-mortar closure and 1 protection/end cap. Dimension 140x140mm. Suitable for designer vents measuring 80 and 100mm in diameter.


B1090 Plenum L 200x200mm - 2 couplings (for Flex HDPE)

Inlet/extraction plenum with 2 side couplings Ø80mm (for HDPE 75/63). Including anti-mortar closure and 2 protection/end caps. Dimension 200x200mm. Suitable for designer vents measuring 125 and 150mm in diameter.


B1097 Plenum P 140x140mm - 1 coupling (for Flex HDPE)

Inlet/extraction plenum with 1 rear coupling Ø80mm (for HDPE 75/63). Including anti-mortar closure and 1 protection/end cap. Suitable for designer vents measuring 80 and 100mm in diameter.


B1100 Plenum P 200x200mm - 2 couplings (for Flex HDPE)

Inlet/extraction plenum with 2 rear couplings Ø80mm (for HDPE 75/63). Including anti-mortar closure and 2 protection/end caps. Suitable for designer vents measuring 125 and 150mm in diameter.


B1106 CAL80 damper

Flow rate regulator damper, designed to be attached to the vents Ø80mm of the inlet/extraction plenum or distribution plenum, made of polypropylene, with quick-fit system, including wing-shaped fins to ensure maximum acoustic comfort. Pack of three.


B1107 METAL EST 125 valve

Valid for extraction in RAL 9010 coated steel, Ø125mm, manually and progressively adjustable.


B1108 PP EST-MM 125 valve

Valid for extraction/inlet in white PP, Ø125mm, manually and progressively adjustable.


B1109 METAL IMM 125 valve

Valid for inlet in RAL 9010 coated steel, Ø125mm, manually and progressively adjustable.



Remote controls

B1061

Control-S 2 recessed modules

Remote control for HRV unit with heat recovery, including 3 switches. Option to select 3 speeds and enable free-cooling mode. 230V~ 50/60Hz.



B1062

Control-S 3 recessed modules

Remote control for HRV unit with heat recovery, including 3 switches. Option to select 3 speeds and enable free-cooling mode. 230V~ 50/60Hz. Version for recessed installation with 3 modules suitable for box 503.



B1063

Control-S wall installation

Remote control for HRV unit with heat recovery, including 3 switches. Option to select 3 speeds and enable free-cooling mode. 230V~ 50/60Hz.



Other accessories

B1060

F7 filter box

External cassette including F7 filter with galvanised metal sheet pre-coated with RAL 9010 and attachment with 125mm attachment. Suitable for CX 120, CX180 and CX28



F7 filters

Class F7 filtration elements (pack of 1 item).

B1079	For Sitali CX 120
B1081	For Sitali CX 180
B1083	For Sitali CX 280
B1085	For Sitali CX 400-550



G4 filters

Class G4 filtration elements (pack of 2 items).

B1080	For Sitali CX 120
B1082	For Sitali CX 180
B1084	For Sitali CX 280
B1086	For Sitali CX 400 - 550



M5 filters

Class M5 filtration elements (pack of 2 items).

B1207	For Sitali CX 280 S1
--------------	----------------------

