

PORTABLE DEHUMIDIFIERS

# AQUARIA S1 24

[P]

|                  |  |
|------------------|--|
| Size             | <b>24</b>                                  |
| For rooms up to  | <b>100 m<sup>3</sup></b>                   |
| Filtration       | <b>antidust   activated carbons   HEPA</b> |
| Application      | <b>residential</b>                         |
| Wireless control | <b>✓</b>                                   |



### Advanced air treatment

Effective both against dust and unpleasant odours, and capable of reducing pollutant particles down to 0.3 microns, thanks to integrated HEPA filters. Going beyond its primary dehumidification function, it serves as a complete year-round air treatment solution.

### Italian design

The touchscreen control panel, backlit front display (deactivatable) and motorised flap create a total flat aesthetic that not only integrates seamlessly into the environment, but also improves user experience.

### TECHNICAL INFO

- Semi-transparent and removable 5L canister with handle
- Condensate drain for continuous operation
- Temperature and humidity indicator
- Front display with color change depending on humidity detected
- 3 ventilation speeds
- Handy side handles and swivel wheels



- Dehumidification
- Children's Lock
- Laundry
- Full Tank Signal
- Vertical swing
- Timer



## TECHNICAL DATA

|   |     |                   | Aquaria S1 24 P  |
|---|-----|-------------------|------------------|
| Product code  |     |                   | 02065            |
| EAN code  |     |                   | 8021183020656    |
| Dehumidification capacity                               | (1) | l/24h             | 24               |
| Max. power absorption in dehumidification mode          | (1) | W                 | 360              |
| Maximum absorption in dehumidification mode             | (1) | A                 | 1,8              |
| Max. power absorption in dehumidification mode (U.L.U.) |     | W                 | 380              |
| Degree of protection                                    |     |                   | IPX0             |
| Fan speed   |     | nr                | 3                |
| Tank capacity   |     | l                 | 5                |
| Air flow rate (max)                                     |     | m <sup>3</sup> /h | 180              |
| Sound pressure  |     | dB(A)             | 38               |
| Product dimensions (W x H x D with wheels)              |     | mm                | 367 x 610 x 274  |
| Gift box dimensions (WxHxD)                             |     | mm                | 421 x 664 x 335  |
| Weight (without packaging)                              |     | kg                | 14,6             |
| Weight (with packaging)                                 |     | kg                | 16,1             |
| Refrigerant gas   |     |                   | R290             |
| GWP (Global Warming Potential)                          |     |                   | 3                |
| Refrigerant gas charge                                  |     | kg                | 0,052            |
| Minimum floor area for installation, use and storage    |     | m <sup>2</sup>    | 4                |
| Power supply  |     | V-F-Hz            | 220-240 - 1 - 50 |
| Antidust filter   |     |                   | ✓                |
| Activated carbon filter                                 |     |                   | ✓                |
| HEPA filter   |     |                   | ✓                |
| Continuous drainage operation                           |     |                   | ✓                |
| Adjustable electronic humidistat                        |     |                   | ✓                |
| Display of room humidity                                |     |                   | ✓                |
| Display of room temperature                             |     |                   | ✓                |
| Full tank indicator                                     |     |                   | ✓                |
| Child lock  |     |                   | ✓                |
| Flap oscillation  |     |                   | ✓                |
| Laundry function  |     |                   | ✓                |
| Timer   |     |                   | ✓                |
| Visible water level                                     |     |                   | ✓                |
| Defrosting device                                       |     |                   | ✓                |
| Hot gas defrost system                                  |     |                   | -                |
| Wireless control  |     |                   | ✓                |

## LIMITS OF OPERATING CONDITIONS

|                    |                               |         |
|--------------------|-------------------------------|---------|
| Indoor environment | Maximum operating temperature | DB 32°C |
|                    | Minimum operating temperature | DB 5°C  |

(1) DB 30°C - WB 27°C (30°C-80%)  
(U.L.U.) DB 32°C - WB 23°C