

DOLCECLIMA BREZZA 14 HP

14,000 BTU/h* of power. Also in heat pump

Cod. 02258



HEAT PUMP

Heat pump air conditioner. Thanks to this feature you can replace or support traditional heating in intermediate seasons.



MOTORIZED FLAPS WITH AUTO-SWING

The air flow can be easily directed in the room, thanks to the motorized flap on the top of the unit



WI-FI AND VOICE CONTROL

Thanks to the integrated Wi-Fi and compatibility with the most common voice controllers, it can be managed with either voice commands or using the dedicated app.



TOUCH SCREEN AND HIDDEN DISPLAY

Touch-screen control panel with minimal aesthetic impact and backlit front display (can be deactivated) for immediate temperature control.

FEATURES

Rated cooling capacity: 3.5 kW**

Energy class: A / in heating A

Sound pressure: 65 dB (A)

Rated energy efficiency index: EER 2.6**

Coolant gas: R290

Anti-dust filter

Multi-function remote control and LCD display

Convenient side handles and wheels

Motorised flap

Window and air ejection hose kit included.

FUNCTIONS

Cooling, heating, dehumidification and ventilation

24 H timer

Sleep function: gradually increases the set temperature and ensures reduced noise for better night-time well-being.

Auto-Restart function: after a power failure, it restarts at the last function set.

* Test conditions: maximum cooling power (35°C / 80% RH).

** Test conditions: according to the EN 14511 standard.



		DOLCECLIMA BREZZA 9 EQ WIFI	DOLCECLIMA BREZZA 10 HP WIFI	DOLCECLIMA BREZZA 14 HP WIFI	DOLCECLIMA EASY 10 P
PRODUCT CODE		02259	02257	02258	02058
EAN CODE		8021183022599	8021183022575	8021183022582	8021183020588
Nominal cooling capacity (1)	Prated	kW			
Nominal heating capacity (1)	Prated	kW	-		
Nominal power consumption for cooling (1)	PEER	kW	0,96	1,0	1,35
Nominal absorption for cooling (1)		A	4,3	4,3	5,9
Nominal power consumption for heating (1)	PCOP	kW	-	0,91	1,15
Nominal absorption for heating (1)		A	-	4,1	6,3
Nominal energy efficiency index (1)	EERd		2,6	2,6	2,6
Nominal efficiency coefficient (1)	COPd		-	2,3	2,3
Energy efficiency class in cooling (1)					
Energy efficiency class in heating (1)			-		
Energy consumption in "thermostat off" mode	PTO	W	-	-	1
Energy consumption in "standby" mode (EN 62301)	PSB	W	0,5	0,5	0,5
Hourly electricity consumption for single duct (1) cooling mode	QSD	kWh/h	0,96	1,0	1,35
Hourly electricity consumption for single duct (1) heating mode	QSD	kWh/h	-	0,91	1,15
Supply voltage		V-F-Hz	220/240-1-50	220/240-1-50	220/240-1-50
Supply voltage (min/max)		V	198 / 253	198 / 253	198 / 264
Maximum power consumption in cooling mode (1)		W	1000	1100	1346
Maximum absorption in cooling mode (1)		A	4,5	4,9	5,9
Maximum power consumption in heating mode (4)		W	-	1050	1391
Maximum absorption in heating mode (4)		A	-	4,7	6,3
Dehumidification capacity (2)		l/h	1,4	1,4	3,2
Air flow rate (max/med/min)		m³/h	300 / 270 / 240	300 / 270 / 240	330 / 300 / 270
Fan speed			3	3	3
Flexible pipe (length x diameter)		mm	1500 x 150	1500 x 150	1500 x 130
Maximum remote control range (distance/angle)		m / °	5 / ±45°	5 / ±45°	5 / ±45°
Dimensions (WxHxD) (without packaging)		mm	440 x 683 x 357	440 x 683 x 357	440 x 683 x 357
Dimensions (WxHxD) (with packaging)		mm	474 x 885 x 376	474 x 885 x 376	474 x 885 x 376
Weight (without packaging)		kg	30	30	31
Weight (with packaging)		kg	33	33	34
Sound pressure level (min-max) (3)		dB(A)	43-45	-	-
Sound power level (indoor only) (EN 12102)	LWA	dB(A)			
Degree of protection provided by covers			IPX0	IPX0	IPX0
Refrigerant gas (5)		Type	R290	R290	R290
Global warming potential	GWP		3	3	3
Refrigerant gas charge		kg	0,27	0,21	0,23
Maximum operating pressure		MPa	2,6	2,6	2,6
Maximum operating pressure (low pressure side)		MPa	1,0	1,0	1,0
Lower flammable limit	LFL	kg/m³	0,038	0,038	0,038
Minimum floor area for installation, use and storage		m²	10	10	11
Power cable (N° pole x section mm²)			3 x 1,0	3 x 1,0	3 x 1,0
Fuse			3,15 A	3,15 A	3,15 A
Conformity mark			CE	CE	CE
Integrated Wi-Fi			✓	✓	✓

LIMITS OF OPERATING CONDITIONS

Indoor ambient temperature	Maximum temperature in cooling	DB 35°C - WB 28°C	DB 35°C - WB 28°C	DB 35°C - WB 28°C	DB 35°C - WB 32°C
	Minimum temperature in cooling	DB 18°C - WB 12°C	DB 18°C - WB 12°C	DB 18°C - WB 12°C	DB 16°C
	Maximum temperature in heating	-	DB 27°C - WB 19°C	DB 27°C - WB 19°C	-
	Minimum temperature in heating	-	DB 7°C - WB 6°C	DB 7°C - WB 6°C	-

(1) Test conditions: the data refer to the EN14511 standard.

(2) Test conditions in dehumidification mode: DB 30°C WB 27,1°C

(3) Declaration of test data in a semi-anechoic chamber at a distance of 2 m, minimum pressure in ventilation only

(4) High load test and maximum heating output

(5) Hermetically sealed equipment.