

FAN HEATERS

CALDO HUMI T



Maximum power	2 kW
For rooms up to	60 m³
Type	Ceramic heating element
Installation	Mobile



Built-in humidifier

It helps keep the air pleasantly balanced, counteracting the dryness typical of the winter months and making the environment more comfortable and cozy for the whole family.

An experience of superior comfort

Setting the desired temperature and activating the automatic airflow oscillation is quick and easy using the touchscreen panel or the included remote control.



-  Heating
-  Ventilation
-  Humidification
-  Oscillation
-  Maximum power
-  Minimum power
-  Temperature setting
-  Timer

TECHNICAL INFO

- Room and Safety Thermostat
- Overheating protection
- Automatic shut-off if the unit tips over
- Convenient handle
- Base mounting system with a twist-lock mechanism, no screws required
- In humidification mode, the chromotherapy indicator displays the current status: orange (heating) or green (ventilation), depending on the set point relative to the room temperature.
- 12-hour timer programming



NEW

TECHNICAL DATA		Caldo Pocket	Caldodesign	Caldo Flick	Caldo Cubic
Product code		99229	99447	99183	99228
EAN code		8021183992298	8021183994476	8021183991833	8021183992281
Resistance		Ceramics	Ceramics	Ceramics	Ceramics
Thermal power (Max)	W	1500	1800	1800	1800
Power settings		ONLY FAN / 1000 / 1500	ONLY FAN / 1000 / 1800	ONLY FAN / 1000 / 1800	ONLY FAN / 900 / 1800
Heating volume (max)	m ³	50	55	55	55
Dimensions (WxHxD)	mm	159 x 219 x 98	245 x 248 x 216	140 x 248 x 167	165 x 215 x 145
Gift box dimensions (WxHxD)	mm	169 x 240 x 106	275 x 275 x 235	150 x 270 x 175	183 x 230 x 183
Master dimensions (W x H x D)	mm	552 x 495 x 180	750 x 290 x 570	465 x 550 x 185	378 x 247 x 378
Units per master	nr	10	6	6	4
Weight (without packaging)	kg	1,1	1,8	1,3	1,6
Weight (with packaging)	kg	1,2	2,2	1,6	1,8
Insulation class		II	II	II	II
Degree of protection of enclosures		IPX0	IPX0	IPX0	IP21
Electrical power supply	V-F-Hz	220-240 - 1 - 50/60	220-240 - 1 - 50	220-240 - 1 - 50	220-240 - 1 - 50/60
Conformity Markings		CE	CE	CE	CE
Timer		-	-	-	-
Room thermostat		✓	✓	✓	✓
Safety thermostat		✓	✓	✓	✓
Ventilation function		✓	✓	✓	✓
Oscillating function		-	-	✓	-
Anti-tip switch		✓	-	✓	✓
Anti-ice function		✓	✓	-	✓
Power selector		✓	✓	✓	✓
Eco Function		-	-	-	-
Remote control		-	-	-	-
Tilt adjustment		-	✓	-	-
Wireless control		-	-	-	-
Wall-mounted position		-	-	-	-
Tabletop position		✓	✓	✓	✓

NEW

NEW

TECHNICAL DATA		Caldo Trendy	Caldo Humi T	Caldo Line [NW]
Product code		99268	99178	99177
EAN code		8021183992687	8021183991789	8021183991772
Resistance		Ceramics	Ceramics	Ceramics
Thermal power (Max)	W	1800	2000	2000
Power settings		900 / 1800	ONLY FAN / 1200 / 2000	ONLY FAN / 1300 / 2000
Heating volume (max)	m ³	55	60	60
Dimensions (WxHxD)	mm	216 x 284 x 125	230 x 600 x 230	233 x 659 x 187
Gift box dimensions (WxHxD)	mm	262 x 316 x 150	202 x 634 x 178	242 x 698 x 202
Master dimensions (W x H x D)	mm	465 x 647 x 277	650 x 380 x 425	-
Units per master	nr	6	4	-
Weight (without packaging)	kg	1,7	1,8	2,8
Weight (with packaging)	kg	2,0	2,2	4,0
Insulation class		II	II	II
Degree of protection of enclosures		IP21	IPX0	IPX0
Electrical power supply	V-F-Hz	220-240 - 1 - 50	220-240 - 1 - 50	220-240 - 1 - 50
Conformity Markings		CE	CE	CE
Timer		✓	✓	✓
Room thermostat		✓	✓	✓
Safety thermostat		✓	✓	✓
Ventilation function		-	✓	✓
Oscillating function		✓	✓	✓
Anti-tip switch		✓	✓	✓
Anti-ice function		-	-	✓
Power selector		✓	✓	✓
Eco Function		✓	-	✓
Remote control		-	✓	✓
Tilt adjustment		-	-	-
Wireless control		-	-	✓
Tabletop position		✓	✓	✓
Wall-mounted position		-	-	-