

DOLCECLIMA EASY 10

10,000 BTU/h* of power in console format

Cod. 02058



CONSOLE FORMAT



Only 66 cm high and 27 cm deep, for easy placement in any room of the house

ROTATING CASTORS



It can be easily transported and moved in any direction, thanks to its 360 degree rotation.

TOUCHSCREEN DISPLAY



Touch-screen control panel, with minimal aesthetic impact, for immediate control.

FOLLOW ME



The remote control acts as a remote thermostat to ensure correct temperature control in the point where the occupants are present in the room.

FEATURES

Cooling capacity: 2.4 kW**

Energy class: **A**

Sound pressure: 60 dB (A)

Rated energy efficiency index: EER 2.6**

Coolant gas: R290

Anti-dust filter

Multi-function remote control and LCD display

Convenient side handles and wheels

Air ejection hose kit included.

FUNCTIONS

Cooling, dehumidification and ventilation (3 speeds)

24 H timer

Auto function: optimises energy consumption, adjusting the cooling in relation to the room temperature.

Sleep function: gradually increases the set temperature for greater acoustic comfort.

Turbo function: maximum ventilation speed for super cooling.

Follow Me function: precise temperature detection in the point where the remote control is located.

Auto-Restart function: after a power failure, it restarts at the last function set.

* Test conditions: maximum cooling power (35°C / 80% RH).

** Test conditions: according to the EN 14511 standard.



		DOLCECLIMA BREZZA 9 EQ WIFI	DOLCECLIMA BREZZA 10 HP WIFI	DOLCECLIMA BREZZA 14 HP WIFI	DOLCECLIMA EASY 10 P
PRODUCT CODE		02259	02257	02258	02058
EAN CODE		8021183022599	8021183022575	8021183022582	8021183020588
Nominal cooling capacity (1)	Prated	kW			
Nominal heating capacity (1)	Prated	kW	-		
Nominal power consumption for cooling (1)	PEER	kW	0,96	1,0	1,35
Nominal absorption for cooling (1)		A	4,3	4,3	5,9
Nominal power consumption for heating (1)	PCOP	kW	-	0,91	1,15
Nominal absorption for heating (1)		A	-	4,1	6,3
Nominal energy efficiency index (1)	EERd		2,6	2,6	2,6
Nominal efficiency coefficient (1)	COPd		-	2,3	2,3
Energy efficiency class in cooling (1)					
Energy efficiency class in heating (1)			-		
Energy consumption in "thermostat off" mode	PTO	W	-	-	1
Energy consumption in "standby" mode (EN 62301)	PSB	W	0,5	0,5	0,5
Hourly electricity consumption for single duct (1) cooling mode	QSD	kWh/h	0,96	1,0	1,35
Hourly electricity consumption for single duct (1) heating mode	QSD	kWh/h	-	0,91	1,15
Supply voltage		V-F-Hz	220/240-1-50	220/240-1-50	220/240-1-50
Supply voltage (min/max)		V	198 / 253	198 / 253	198 / 264
Maximum power consumption in cooling mode (1)		W	1000	1100	1346
Maximum absorption in cooling mode (1)		A	4,5	4,9	5,9
Maximum power consumption in heating mode (4)		W	-	1050	1391
Maximum absorption in heating mode (4)		A	-	4,7	6,3
Dehumidification capacity (2)		l/h	1,4	1,4	3,2
Air flow rate (max/med/min)		m³/h	300 / 270 / 240	300 / 270 / 240	330 / 300 / 270
Fan speed			3	3	3
Flexible pipe (length x diameter)		mm	1500 x 150	1500 x 150	1500 x 130
Maximum remote control range (distance/angle)		m / °	5 / ±45°	5 / ±45°	5 / ±45°
Dimensions (WxHxD) (without packaging)		mm	440 x 683 x 357	440 x 683 x 357	440 x 683 x 357
Dimensions (WxHxD) (with packaging)		mm	474 x 885 x 376	474 x 885 x 376	474 x 885 x 376
Weight (without packaging)		kg	30	30	31
Weight (with packaging)		kg	33	33	34
Sound pressure level (min-max) (3)		dB(A)	43-45	-	-
Sound power level (indoor only) (EN 12102)	LWA	dB(A)			
Degree of protection provided by covers			IPX0	IPX0	IPX0
Refrigerant gas (5)		Type	R290	R290	R290
Global warming potential	GWP		3	3	3
Refrigerant gas charge		kg	0,27	0,21	0,23
Maximum operating pressure		MPa	2,6	2,6	2,6
Maximum operating pressure (low pressure side)		MPa	1,0	1,0	1,0
Lower flammable limit	LFL	kg/m³	0,038	0,038	0,038
Minimum floor area for installation, use and storage		m²	10	10	11
Power cable (N° pole x section mm²)			3 x 1,0	3 x 1,0	3 x 1,0
Fuse			3,15 A	3,15 A	3,15 A
Conformity mark			CE	CE	CE
Integrated Wi-Fi			✓	✓	✓

LIMITS OF OPERATING CONDITIONS

Indoor ambient temperature	Maximum temperature in cooling	DB 35°C - WB 28°C	DB 35°C - WB 28°C	DB 35°C - WB 28°C	DB 35°C - WB 32°C
	Minimum temperature in cooling	DB 18°C - WB 12°C	DB 18°C - WB 12°C	DB 18°C - WB 12°C	DB 16°C
	Maximum temperature in heating	-	DB 27°C - WB 19°C	DB 27°C - WB 19°C	-
	Minimum temperature in heating	-	DB 7°C - WB 6°C	DB 7°C - WB 6°C	-

(1) Test conditions: the data refer to the EN14511 standard.

(2) Test conditions in dehumidification mode: DB 30°C WB 27,1°C

(3) Declaration of test data in a semi-anechoic chamber at a distance of 2 m, minimum pressure in ventilation only

(4) High load test and maximum heating output

(5) Hermetically sealed equipment.