

PELER 4D

The compact, practical and technological air cooler

Cod. 99308



TOP TO BOTTOM FILLING

The tank doesn't need to be removed from the lower part



TOUCHSCREEN DISPLAY

Touch-screen control panel, with minimal aesthetic impact, for immediate control.



HORIZONTAL SWING

Continuous and automatic orientation of air flow from right to left



INTEGRATED TIMER





Automatic shut-down programmable up to 8 hours


FEATURES

- Maximum power consumption: 75W
- Air flow rate (maximum): 350 m³/h
- Air speed (maximum): 7 m/s
- Maximum sound power level: 57 dB(A)
- Tank capacity: 4 lt
- Touch control panel
- Practical wheels for transportation
- Horizontal oscillation mode of the air flow
- Remote control included
- Timer up to 8 h
- 3 ventilation speeds (low, medium, high)
- 3 operating modes (normal, natural, rest)
- Ice box included



Evaporative coolers

| | | PELER 4D | PELER 6C | PELER 10 WIFI | PELER 20 |
|-------------------------------|---------|--|--|--|--|
| PRODUCT CODE | | 99308 | 99310 | 99242 | 99355 |
| EAN CODE | | 8021183993080 | 8021183993103 | 8021183992427 | 8021183993554 |
| Electrical power supply | V/F/Hz | 220-240 /1/50 - 60 | 220-240/1/50-60 | 220-240/1/50-60 | 220-240/1/50 |
| Maximum power absorption | W | 75 | 75 | 60 | 110 |
| Stand-by power consumption | W | - | 0,4 | ≤1 | 0,45 |
| Fan speed | n | 3 | 3 | 3 | 4 |
| Air flow rate (maximum) | m³/h | 350 | 450 | 200 | 600 |
| Air speed (maximum) | m/s | 7 | 8,5 | 5 | 9,0 |
| Sound pressure level (1) | dB(A) | - | 50 | 44 | 51 |
| Maximum Sound power level (1) | dB(A) |  57 |  62 |  55 |  60 |
| Insulation class | | II | II | II | II |
| Power cable | n / mm² | 2 x 0,75 | 2 x 0,75 | 2 x 0,75 | 2 x 0,75 |
| Water tank capacity | l | 4 | 6,0 | 10,0 | 20,0 |
| Evaporative sheet | | Honeycomb | Honeycomb | Honeycomb | Honeycomb |
| Control panel | | Touch | Touch | Touch | Touch |
| Conformity mark | | CE | CE | CE | CE |
| Dimensions (WxHxD) | mm | 235 x 610 x 260 | 260 x 700 x 300 | 264 x 770 x 270 | 342 x 897 x 390 |
| Gift box dimensions (WxHxD) | mm | 285 x 630 x 310 | 316 x 792 x 355 | 337 x 870 x 340 | 405 x 960 x 440 |
| Weight (without packaging) | kg | 4,5 | 6,6 | 6,8 | 8,0 |
| Weight (with packaging) | kg | 5,5 | 7,6 | 8,0 | 10,5 |
| Timer | | ✓ | ✓ | ✓ | ✓ |
| Removable water tank | | ✓ | ✓ | ✓ | ✓ |
| Oscillating function | | ✓ | ✓ | ✓ | ✓ |
| Remote control | | ✓ | ✓ | ✓ | ✓ |
| Ionizer | | - | ✓ | - | - |
| Power off switch | | - | - | ✓ | ✓ |
| Power supply cable housing | | - | - | - | ✓ |

| | | PELER TOWER |
|-------------------------------|---------|--|
| PRODUCT CODE | | 99312 |
| EAN CODE | | 8021183993127 |
| Electrical power supply | V/F/Hz | 220-240/1/50 |
| Maximum power absorption | W | 65 |
| Stand-by power consumption | W | - |
| Fan speed | n | 3 |
| Air flow rate (maximum) | m³/h | 300 |
| Air speed (maximum) | m/s | 6 |
| Sound pressure level (1) | dB(A) | 50-52 |
| Maximum Sound power level (1) | dB(A) |  64 |
| Insulation class | | II |
| Power cable | n / mm² | 2 x 0,75 |
| Water tank capacity | l | 3,5 |
| Evaporative sheet | | Honeycomb |
| Control panel | | Touch |
| Conformity mark | | CE |
| Dimensions (WxHxD) | mm | 320 x 1100 x 320 |
| Gift box dimensions (WxHxD) | mm | 245 x 1125 x 230 |
| Weight (without packaging) | kg | 5,0 |
| Weight (with packaging) | kg | 6,0 |
| Timer | | ✓ |
| Removable water tank | | - |
| Oscillating function | | ✓ |
| Remote control | | ✓ |
| Ionizer | | ✓ |
| Power off switch | | - |
| Power supply cable housing | | - |

(1) Test conditions: the sound pressure was measured in a semi-anechoic chamber at a distance of 2 metres from the front part of the appliance (at a distance of 1 metre for code 99242) with the microphone at a height of 1 metre. During measurement, all device functions are enabled except swing (if present).